

```

<?xml version="1.0" encoding="UTF-8" ?>
- <TEI xmlns="http://www.tei-c.org/ns/1.0" xmlns:rng="http://relaxng.org/ns/structure/1.0"
  xmlns:s="http://www.ascc.net/xml/schematron" xml:lang="en" n="enrich">
- <teiHeader>
- <fileDesc>
  - <titleStmt>
    <title>TEI P5 schema for ENRICH-WAMCP</title>
  </titleStmt>
  - <editionStmt>
    <edition>0.1</edition>
  </editionStmt>
  - <publicationStmt>
    <authority>CCH</authority>
  - <address>
    - <addrLine>
      <email>elena.pierazzo@kcl.ac.uk</email>
    </addrLine>
    - <addrLine>
      <email>gerhard.brey.@kcl.ac.uk</email>
    </addrLine>
    </address>
  </publicationStmt>
  - <sourceDesc>
    <p>authored from scratch</p>
  </sourceDesc>
</fileDesc>
- <revisionDesc>
  <change who="EP" when="2009-12-04">Modified WP3_deliv_1.xml file</change>
</revisionDesc>
</teiHeader>
- <text>
- <body>
  - <div xml:id="ENRICHWACMPPODD">
    <head>Customization Section</head>
  - <p>
    We include in the schema the four basic key TEI modules
    <ident>header</ident>
    ,
    <ident>core</ident>
    ,
    <ident>tei</ident>
    , and
    <ident>textstructure</ident>
    . We also include five specialized modules:
    <ident>msdescription</ident>
    ,
    <ident>linking</ident>
    ,
    <ident>namesdates</ident>
    ,
    <ident>figures</ident>
    , and
    <ident>transcr</ident>
    .
  </p>
  - <p>
    All the elements and attributes defined by these modules are included in the
    ENRICH schema, with the following modifications. Firstly, several unwanted
    elements are deleted. Secondly, some optional attributes have been made
    compulsory, and their range of possible values are constrained. Finally, the content
    model for a small number of elements has been simplified to remove unwanted
    alternatives.
    <hi rend="bold">Added for WAMCP</hi>
    : the content of one element has been modified and a consequent feature request
    has been made to the TEI .
  </p>
  - <p>
    The following elements are deleted:
    <gi>ab</gi>
    ,

```

<gi>alt</gi>  
,  
<gi>altGrp</gi>  
,  
<gi>analytic</gi>  
,  
<gi>appInfo</gi>  
,  
<gi>application</gi>  
,  
<gi>biblFull</gi>  
,  
<gi>biblStruct</gi>  
,  
<gi>binaryObject</gi>  
,  
<gi>broadcast</gi>  
,  
<gi>cRefPattern</gi>  
,  
<gi>cell</gi>  
,  
<gi>cit</gi>  
,  
<gi>climate</gi>  
,  
<gi>correction</gi>  
,  
<gi>distinct</gi>  
,  
<gi>email</gi>  
,  
<gi>emph</gi>  
,  
<gi>equipment</gi>  
,  
<gi>equiv</gi>  
,  
<gi>fsdDecl</gi>  
,  
<gi>headItem</gi>  
,  
<gi>headLabel</gi>  
,  
<gi>hyphenation</gi>  
,  
<gi>imprint</gi>  
,  
<gi>interpretation</gi>  
,  
<gi>join</gi>  
,  
<gi>joinGrp</gi>  
,  
<gi>link</gi>  
,  
<gi>linkGrp</gi>  
,  
<gi>listNym</gi>  
,  
<gi>measure</gi>  
,  
<gi>measureGrp</gi>  
,  
<gi>meeting</gi>  
,  
<gi>mentioned</gi>  
,  
<gi>metDecl</gi>  
,

<gi>metSym</gi>  
,  
<gi>monogr</gi>  
,  
<gi>msItemStruct</gi>  
,  
<gi>namespace</gi>  
,  
<gi>normalization</gi>  
,  
<gi>num</gi>  
,  
<gi>nym</gi>  
,  
<gi>postBox</gi>  
,  
<gi>postCode</gi>  
,  
<gi>q</gi>  
,  
<gi>quotation</gi>  
,  
<gi>recording</gi>  
,  
<gi>recordingStmt</gi>  
,  
<gi>refsDecl</gi>  
,  
<gi>rendition</gi>  
,  
<gi>row</gi>  
,  
<gi>rs</gi>  
,  
<gi>said</gi>  
,  
<gi>samplingDecl</gi>  
,  
<gi>scriptStmt</gi>  
,  
<gi>segmentation</gi>  
,  
<gi>series</gi>  
,  
<gi>soCalled</gi>  
,  
<gi>sp</gi>  
,  
<gi>speaker</gi>  
,  
<gi>stage</gi>  
,  
<gi>state</gi>  
,  
<gi>stdVals</gi>  
,  
<gi>street</gi>  
,  
<gi>table</gi>  
,  
<gi>tagUsage</gi>  
,  
<gi>tagsDecl</gi>  
,  
<gi>teiCorpus</gi>  
,  
<gi>terrain</gi>  
,  
<gi>time</gi>  
,

```

<gi>timeline</gi>
'
<gi>variantEncoding</gi>
'
<gi>when</gi>
.
</p>
- <p>
  The
  <ident type="class">att.global.linking</ident>
  class is also deleted, since we anticipate no need for complex pointing mechanisms.
</p>
- <p>
  On the
  <gi>altIdentifier</gi>
  element, the
  <att>type</att>
  attribute is compulsory, and must take one of the following values:
  <val>former</val>
  ;
  <val>partial</val>
  ;
  <val>internal</val>
  ;
  <val>system</val>
  ;
  <val>other</val>
</p>
- <p>
  On the
  <gi>availability</gi>
  element, the
  <att>status</att>
  attribute is compulsory, and must take one of the following values:
  <val>free</val>
  ;
  <val>unknown</val>
  ;
  <val>restricted</val>
  .
</p>
- <p>
  On the
  <gi>biblScope</gi>
  element, the
  <att>type</att>
  attribute is compulsory, and must take one of the following values:
  <val>volume</val>
  ;
  <val>pages</val>
  .
</p>
- <p>
  On the
  <gi>custEvent</gi>
  element, the
  <att>type</att>
  attribute is compulsory, and must take one of the following values:
  <val>check</val>
  ;
  <val>conservation</val>
  ;
  <val>description</val>
  ;
  <val>exhibition</val>
  ;
  <val>loan</val>
  ;
  <val>photography</val>
  ;

```

```

    <val>other</val>
    .
</p>
- <p>
  On the
  <gi>decoNote</gi>
  element, the
  <att>type</att>
  attribute is compulsory, and must take one of the following values:
  <val>border</val>
  ;
  <val>diagram</val>
  ;
  <val>initial</val>
  ;
  <val>marginal</val>
  ;
  <val>miniature</val>
  ;
  <val>mixed</val>
  ;
  <val>paratext</val>
  ;
  <val>secondary</val>
  ;
  <val>other</val>
  ;
  <val>illustration</val>
  ;
  <val>printmark</val>
  ;
  <val>publishmark</val>
  ;
  <val>vignette</val>
  ;
  <val>frieze</val>
  ;
  <val>map</val>
  ;
  <val>unspecified</val>
  .
  <hi rend="bold">Added for WAMCP:</hi>
  <val>unwan</val>
  ,
  <val>rubrication</val>
  ,
  <val>tooling</val>
  .
</p>
- <p>
  On the
  <gi>dimensions</gi>
  element, the
  <att>type</att>
  attribute is compulsory, and must take one of the following values:
  <val>leaf</val>
  ;
  <val>binding</val>
  ;
  <val>slip</val>
  ;
  <val>written</val>
  ;
  <val>boxed</val>
  ;
  <val>unknown</val>
  .
  <hi rend="bold">Added for WAMCP:</hi>
  <val>line-height</val>
</p>

```

- <p>  
 On the  
 <gi>gap</gi>  
 element, the  
 <att>reason</att>  
 attribute is compulsory, and must take one of the following values:  
 <val>damage</val>  
 ;  
 <val>illegible</val>  
 ;  
 <val>cancelled</val>  
 ;  
 <val>irrelevant</val>  
 .  
 </p>

- <p>  
 On all members of the  
 <ident>att.dimensions</ident>  
 class, the  
 <att>unit</att>  
 attribute is compulsory, and must take one of the following values:  
 <val>chars</val>  
 ;  
 <val>leaves</val>  
 ;  
 <val>lines</val>  
 ;  
 <val>mm</val>  
 ;  
 <val>pages</val>  
 ;  
 <val>words</val>  
 . The  
 <att>precision</att>  
 attribute is removed.  
 </p>

- <p>  
 On the  
 <gi>handNote</gi>  
 element, the  
 <att>script</att>  
 attribute is compulsory, and must take one of the following values (   
 <hi rend="bold">added for WAMCP</hi>  
 )):  
 <val>muhaqqaq</val>  
 ,  
 <val>rayhani</val>  
 ,  
 <val>naskh</val>  
 ,  
 <val>maghribi</val>  
 ,  
 <val>bihari</val>  
 ,  
 <val>nasta\_liq</val>  
 ,  
 <val>thuluth</val>  
 ,  
 <val>tawqi\_</val>  
 ,  
 <val>riqa\_</val>  
 ,  
 <val>ghubar</val>  
 ,  
 <val>ta\_liq</val>  
 ,  
 <val>diwani</val>  
 ,  
 <val>ruq\_ah</val>  
 ,

<val>siyaqah</val>  
 . Values for ENRICH were:  
 <val>carolmin</val>  
 ;  
 <val>textualis</val>  
 ;  
 <val>cursiva</val>  
 ;  
 <val>hybrida</val>  
 ;  
 <val>humbook</val>  
 ;  
 <val>humcursiva</val>  
 ;  
 <val>kanzlei</val>  
 ;  
 <val>kurrent</val>  
 ;  
 <val>other</val>  
 , which have been deleted.  
 </p>

- <p>  
 On the  
 <gi>handNote</gi>  
 element, the  
 <att>scope</att>  
 attribute is compulsory, and must take one of the following values:  
 <val>sole</val>  
 ;  
 <val>major</val>  
 ;  
 <val>minor</val>  
 .  
 </p>

- <p>  
 On the  
 <gi>hi</gi>  
 element, the  
 <att>rend</att>  
 attribute is compulsory, and must take one of the following values:  
 <val>hyphenated</val>  
 ;  
 <val>underline</val>  
 ;  
 <val>double-underline</val>  
 ;  
 <val>bold</val>  
 ;  
 <val>caps</val>  
 ;  
 <val>italic</val>  
 ;  
 <val>sup</val>  
 ;  
 <val>rubric</val>  
 .  
 <hi rend="bold">Added for WAMCP</hi>  
 : added  
 <val>overline</val>  
 .  
 </p>

- <p>  
 On the  
 <gi>layout</gi>  
 element, the  
 <att>columns</att>  
 attribute is compulsory, and must take a numeric value.  
 </p>

- <p>  
 On the

- `<gi>msDesc</gi>`  
 element, the  
`<att>xml:id</att>`  
 attribute is compulsory, and must be a valid XML identifier.  
`</p>`
- `<p>`  
 On the  
`<gi>msDesc</gi>`  
 element, the  
`<att>xml:lang</att>`  
 attribute is compulsory, and must be a valid ISO 639 language code.  
`</p>`
- `<p>`  
 On the  
`<gi>name</gi>`  
 element, the  
`<att>type</att>`  
 attribute is compulsory, and must take one of the following values:  
`<val>person</val>`  
 ;  
`<val>place</val>`  
 ;  
`<val>org</val>`  
 ;  
`<val>unknown</val>`  
 .  
`</p>`
- `<p>`  
 On the  
`<gi>objectDesc</gi>`  
 element, the  
`<att>form</att>`  
 attribute is compulsory, and must take one of the following values:  
`<val>codex</val>`  
 ;  
`<val>leaf</val>`  
 ;  
`<val>scroll</val>`  
 ;  
`<val>other</val>`  
 .  
`</p>`
- `<p>`  
 On the  
`<gi>person</gi>`  
 element, the  
`<att>sex</att>`  
 attribute is compulsory, and must be one of 1 (male), 2 (female), 0 (inapplicable),  
 or 9 (unknown).  
`</p>`
- `<p>`  
 On the  
`<gi>region</gi>`  
 element, the  
`<att>type</att>`  
 attribute is compulsory, and must take one of the following values:  
`<val>parish</val>`  
 ;  
`<val>county</val>`  
 ;  
`<val>compass</val>`  
 ;  
`<val>geog</val>`  
 ;  
`<val>state</val>`  
 ;  
`<val>unknown</val>`  
 .  
`</p>`
- `<p>`



On the  
`<gi>supplied</gi>`  
 element, the  
`<att>reason</att>`  
 attribute is compulsory, and must take one of the following values:  
`<val>omitted</val>`  
 ;  
`<val>illegible</val>`  
 ;  
`<val>damage</val>`  
 ;  
`<val>unknown</val>`  
 .  
`</p>`

- `<p>`  
 On the  
`<gi>supportDesc</gi>`  
 element, the  
`<att>material</att>`  
 attribute is compulsory, and must take one of the following values:  
`<val>perg</val>`  
 ;  
`<val>chart</val>`  
 ;  
`<val>mixed</val>`  
 ;  
`<val>unknown</val>`  
 .  
`</p>`

- `<p>`  
 The following changes do not affect TEI conformance since either they affect only optional parts of TEI content models or they involve additional value constraints for TEI attributes:

- `<list>`

- `<item>`  
 On the  
`<gi>textLang</gi>`  
 element, the  
`<att>mainLang</att>`  
 attribute is compulsory, and must take a legal character identifier as value.  
`</item>`
- `<item>`  
 The optional elements  
`<att>xml:id</att>`  
 and  
`<att>xml:lang</att>`  
 are made mandatory for the  
`<gi>msDesc</gi>`  
 element.  
`</item>`
- `<item>`  
 The content model of the  
`<gi>date</gi>`  
 element is changed to include a schematron rule which enforces an appropriate selection of attributes (one of:  
`<att>when</att>`  
 ,  
`<att>to</att>`  
 and  
`<att>from</att>`  
 , or  
`<att>notAfter</att>`  
 and  
`<att>notBefore</att>`  
 );  
`<hi rend="bold">Added for WAMCP</hi>`  
 : value for  
`<att>calendar</att>`  
 are:  
`<val>Gregorian</val>`

```

,
<val>Julian</val>
,
<val>AM</val>
,
<val>Hijri-shamsi</val>
,
<val>Hijri-qamari</val>
,
<val>Coptic-EoM</val>
,
<val>Alexandrian Iranian-Yazdigird</val>
,
<val>Iranian-Jalali</val>
,
<val>Spanish</val>
,
<val>Ilahi</val>
,
<val>Hindu</val>
,
<val>unknown</val>
,
<val>other</val>
.
<att>calendar</att>
is mandatory.
</item>
- <item>
  The content model of the recordHist element is changed to remove the
  possibility of including the
  <gi>change</gi>
  element here.
</item>
- <item>
  <hi rend="bold">Added for WAMCP</hi>
  : the content model for
  <gi>collection</gi>
  is changed to allow nestable
  <gi>collection</gi>
  . The element is now member of att.typed.
</item>
</list>
</p>
<!-- select modules -->
- <schemaSpec ident="enrich-wamcp" start="TEI msDesc teiHeader">
  <moduleRef key="header" />
  <moduleRef key="core" />
  <moduleRef key="tei" />
  <moduleRef key="textstructure" />
  <moduleRef key="msdescription" />
  <moduleRef key="linking" />
  <moduleRef key="namesdates" />
  <moduleRef key="figures" />
  <moduleRef key="transcr" />
  <moduleRef key="gaiji" />
  <!-- delete uninteresting classes -->
  <classSpec ident="att.global.linking" mode="delete" type="atts" />
  <classSpec ident="att.dataable.iso" type="atts" mode="delete" />
  <classSpec ident="model.addrPart" type="model" mode="delete" />
  <!-- delete unwanted elements -->
  <elementSpec module="core" ident="address" mode="delete" />
  <elementSpec module="core" ident="analytic" mode="delete" />
  <elementSpec module="core" ident="biblFull" mode="delete" />
  <elementSpec module="core" ident="biblStruct" mode="delete" />
  <elementSpec module="core" ident="binaryObject" mode="delete" />
  <elementSpec module="core" ident="cit" mode="delete" />
  <elementSpec module="core" ident="distinct" mode="delete" />
  <elementSpec module="core" ident="email" mode="delete" />
  <elementSpec module="core" ident="emph" mode="delete" />

```

```

<elementSpec module="core" ident="equiv" mode="delete" />
<elementSpec module="core" ident="headItem" mode="delete" />
<elementSpec module="core" ident="headLabel" mode="delete" />
<elementSpec module="core" ident="imprint" mode="delete" />
<elementSpec module="core" ident="measure" mode="delete" />
<elementSpec module="core" ident="measureGrp" mode="delete" />
<elementSpec module="core" ident="meeting" mode="delete" />
<elementSpec module="core" ident="mentioned" mode="delete" />
<elementSpec module="core" ident="monogr" mode="delete" />
<elementSpec module="core" ident="num" mode="delete" />
<elementSpec module="core" ident="postBox" mode="delete" />
<elementSpec module="core" ident="postCode" mode="delete" />
<elementSpec module="core" ident="refsDecl" mode="delete" />
<elementSpec module="core" ident="rs" mode="delete" />
<elementSpec module="core" ident="said" mode="delete" />
<elementSpec module="core" ident="series" mode="delete" />
<elementSpec module="core" ident="soCalled" mode="delete" />
<elementSpec module="core" ident="sp" mode="delete" />
<elementSpec module="core" ident="speaker" mode="delete" />
<elementSpec module="core" ident="stage" mode="delete" />
<elementSpec module="core" ident="street" mode="delete" />
<elementSpec module="core" ident="teiCorpus" mode="delete" />
<elementSpec module="core" ident="time" mode="delete" />
<elementSpec module="figures" ident="table" mode="delete" />
<elementSpec module="figures" ident="cell" mode="delete" />
<elementSpec module="figures" ident="row" mode="delete" />
<elementSpec module="header" ident="applInfo" mode="delete" />
<elementSpec module="header" ident="application" mode="delete" />
<elementSpec module="header" ident="broadcast" mode="delete" />
<elementSpec module="header" ident="correction" mode="delete" />
<elementSpec module="header" ident="cRefPattern" mode="delete" />
<elementSpec module="header" ident="equipment" mode="delete" />
<elementSpec module="header" ident="fsdDecl" mode="delete" />
<elementSpec module="header" ident="hyphenation" mode="delete" />
<elementSpec module="header" ident="interpretation" mode="delete" />
<elementSpec module="header" ident="metDecl" mode="delete" />
<elementSpec module="header" ident="metSym" mode="delete" />
<elementSpec module="header" ident="namespace" mode="delete" />
<elementSpec module="header" ident="normalization" mode="delete" />
<elementSpec module="header" ident="quotation" mode="delete" />
<elementSpec module="header" ident="recording" mode="delete" />
<elementSpec module="header" ident="recordingStmt" mode="delete" />
<elementSpec module="header" ident="rendition" mode="delete" />
<elementSpec module="header" ident="samplingDecl" mode="delete" />
<elementSpec module="header" ident="scriptStmt" mode="delete" />
<elementSpec module="header" ident="segmentation" mode="delete" />
<elementSpec module="header" ident="state" mode="delete" />
<elementSpec module="header" ident="stdVals" mode="delete" />
<elementSpec module="header" ident="tagUsage" mode="delete" />
<elementSpec module="header" ident="tagsDecl" mode="delete" />
<elementSpec module="header" ident="variantEncoding" mode="delete" />
<elementSpec module="linking" ident="ab" mode="delete" />
<elementSpec module="linking" ident="alt" mode="delete" />
<elementSpec module="linking" ident="altGrp" mode="delete" />
<elementSpec module="linking" ident="join" mode="delete" />
<elementSpec module="linking" ident="joinGrp" mode="delete" />
<elementSpec module="linking" ident="link" mode="delete" />
<elementSpec module="linking" ident="linkGrp" mode="delete" />
<elementSpec module="linking" ident="timeline" mode="delete" />
<elementSpec module="linking" ident="when" mode="delete" />
<elementSpec module="msdescription" ident="msItemStruct" mode="delete" />
<elementSpec module="namesdates" ident="climate" mode="delete" />
<elementSpec module="namesdates" ident="listNym" mode="delete" />
<elementSpec module="namesdates" ident="nym" mode="delete" />
<elementSpec module="namesdates" ident="terrain" mode="delete" />
<elementSpec module="textstructure" ident="argument" mode="delete" />
<elementSpec module="textstructure" ident="byline" mode="delete" />
<elementSpec module="textstructure" ident="closer" mode="delete" />
<elementSpec module="textstructure" ident="dateline" mode="delete" />
<elementSpec module="textstructure" ident="div1" mode="delete" />

```

```

<elementSpec module="textstructure" ident="div2" mode="delete" />
<elementSpec module="textstructure" ident="div3" mode="delete" />
<elementSpec module="textstructure" ident="div4" mode="delete" />
<elementSpec module="textstructure" ident="div5" mode="delete" />
<elementSpec module="textstructure" ident="div6" mode="delete" />
<elementSpec module="textstructure" ident="div7" mode="delete" />
<elementSpec module="textstructure" ident="docDate" mode="delete" />
<elementSpec module="textstructure" ident="epigraph" mode="delete" />
<elementSpec module="textstructure" ident="floatingText" mode="delete" />
<elementSpec module="textstructure" ident="imprimatur" mode="delete" />
<elementSpec module="textstructure" ident="opener" mode="delete" />
<elementSpec module="textstructure" ident="postscript" mode="delete" />
<elementSpec module="textstructure" ident="salute" mode="delete" />
<elementSpec module="textstructure" ident="signed" mode="delete" />
<elementSpec module="textstructure" ident="trailer" mode="delete" />
<!-- constrain attribute values for several elements and also supply defaults
-->
- <elementSpec ident="biblScope" mode="change" module="core">
- <attList>
- <attDef ident="type" mode="change" usage="req">
  <defaultVal>pages</defaultVal>
  - <valList type="closed" mode="replace">
    <valItem ident="volume" />
    <valItem ident="pages" />
  </valList>
</attDef>
</attList>
</elementSpec>
- <elementSpec ident="gap" mode="change" module="core">
- <attList>
- <attDef ident="reason" mode="change" usage="req">
  <desc>gives the reason for omission of this material from the
  transcription.</desc>
  <defaultVal>irrelevant</defaultVal>
  - <valList type="closed" mode="replace">
    - <valItem ident="damage">
      <desc>medium is damaged</desc>
    </valItem>
    - <valItem ident="illegible">
      <desc>material cannot be reliably read</desc>
    </valItem>
    - <valItem ident="cancelled">
      <desc>material can be read but has been cancelled by
      scribe</desc>
    </valItem>
    - <valItem ident="irrelevant">
      <desc>material is not regarded as relevant by the
      transcriber</desc>
    </valItem>
    - <valItem ident="omitted">
      <desc>material omitted by transcriber</desc>
    </valItem>
    - <valItem ident="lacuna">
      <desc>material missing from the source</desc>
    </valItem>
  </valList>
</attDef>
- <attDef ident="unit" mode="change" usage="opt">
  <desc>names the unit used for describing the extent of the gap</desc>
  - <valList type="closed" mode="replace">
    - <valItem ident="chars">
      <desc>written characters</desc>
    </valItem>
    - <valItem ident="leaves">
      <desc>leaves</desc>
    </valItem>
    - <valItem ident="lines">
      <desc>lines</desc>
    </valItem>
    - <valItem ident="mm">

```

```

        <desc>millimetres</desc>
    </valItem>
    - <valItem ident="pages">
        <desc>pages</desc>
    </valItem>
    - <valItem ident="words">
        <desc>words</desc>
    </valItem>
</valList>
<!-- no default!! -->
</attDef>
</attList>
</elementSpec>
- <elementSpec ident="hi" mode="change" module="core">
- <attList>
- <attDef ident="rend" mode="change" usage="req">
- <valList type="closed" mode="replace">
    <valItem ident="hyphenated" />
    <valItem ident="underline" />
    <valItem ident="double-underline" />
    <valItem ident="bold" />
    <valItem ident="caps" />
    <valItem ident="italic" />
    <valItem ident="sup" />
    <valItem ident="rubric" />
    <valItem ident="overline" />
</valList>
</attDef>
</attList>
</elementSpec>
- <elementSpec ident="name" mode="change" module="core">
- <attList>
- <attDef ident="type" mode="change" usage="req">
    <defaultVal>unknown</defaultVal>
- <valList type="closed" mode="replace">
    <valItem ident="person" />
    <valItem ident="place" />
    <valItem ident="org" />
    <valItem ident="unknown" />
</valList>
</attDef>
</attList>
</elementSpec>
- <elementSpec ident="handNote" mode="change" module="msdescription">
- <attList>
- <attDef ident="script" mode="change" usage="req">
    <defaultVal>other</defaultVal>
- <valList type="closed" mode="replace">
    <!-- NEW VALLIST for WAMCP -->
    <valItem ident="muhaqqaq" />
    <valItem ident="rayhani" />
    <valItem ident="rayhani" />
    <valItem ident="naskh" />
    <valItem ident="maghribi" />
    <valItem ident="bihari" />
    <valItem ident="nasta_liq" />
    <valItem ident="thuluth" />
    <valItem ident="tawqi_" />
    <valItem ident="riqa_" />
    <valItem ident="ghubar" />
    <valItem ident="ta_liq" />
    <valItem ident="diwani" />
    <valItem ident="ruq_ah" />
    <valItem ident="siyaqah" />
- <!--
    <valItem ident="carolmin"/>
        <valItem ident="textualis"/>
        <valItem ident="cursiva"/>
        <valItem ident="hybrida"/>
        <valItem ident="humbook"/>
        <valItem ident="humcursiva"/>

```

```

        <valItem ident="kanzlei"/>
        <valItem ident="kurrent"/>
        <valItem ident="other">
          <desc>script other than one of these</desc>
        </valItem>
      -->
    - <valItem ident="unknown">
      <desc>script information not available</desc>
    </valItem>
  </valList>
</attDef>
- <attDef ident="scope" mode="change" usage="req">
  <defaultVal>sole</defaultVal>
  - <valList type="closed" mode="replace">
    <valItem ident="sole" />
    <valItem ident="major" />
    <valItem ident="minor" />
  </valList>
</attDef>
</attList>
</elementSpec>
- <elementSpec ident="altIdentifier" module="msdescription" mode="change">
  - <attList>
    - <attDef ident="type" mode="change" usage="req">
      <defaultVal>other</defaultVal>
      - <valList type="closed" mode="replace">
        - <valItem ident="former">
          <desc>former catalogue or shelf number</desc>
        </valItem>
        - <valItem ident="system">
          <desc>former system identifier (Manuscriptorium specific)
          </desc>
        </valItem>
        - <valItem ident="partial">
          <desc>identifier of a previously distinct item</desc>
        </valItem>
        - <valItem ident="internal">
          <desc>internal project identifier</desc>
        </valItem>
        - <valItem ident="other">
          <desc>unspecified</desc>
        </valItem>
      </valList>
    </attDef>
  </attList>
</elementSpec>
- <elementSpec ident="availability" mode="change" module="header">
  - <attList>
    - <attDef ident="status" mode="change" usage="req">
      <defaultVal>unknown</defaultVal>
      - <valList type="closed" mode="replace">
        <valItem ident="free" />
        <valItem ident="unknown" />
        <valItem ident="restricted" />
      </valList>
    </attDef>
  </attList>
</elementSpec>
- <elementSpec ident="textLang" mode="change" module="msdescription">
  - <attList>
    <attDef ident="mainLang" mode="change" usage="req" />
  </attList>
</elementSpec>
- <elementSpec ident="objectDesc" mode="change" module="msdescription">
  - <attList>
    - <attDef ident="form" mode="change" usage="req">
      <defaultVal>codex</defaultVal>
      - <valList type="closed" mode="replace">
        - <valItem ident="codex">
          <desc>a bound codex</desc>

```

```

    </valItem>
  - <valItem ident="leaf">
    <desc>a loose leaf</desc>
  </valItem>
  - <valItem ident="scroll">
    <desc>a scroll</desc>
  </valItem>
  - <valItem ident="other">
    <desc>any other format</desc>
  </valItem>
</valList>
</attDef>
</attList>
</elementSpec>
- <elementSpec ident="supportDesc" mode="change" module="msdescription">
  - <attList>
    - <attDef ident="material" mode="change" usage="req">
      <defaultVal>unknown</defaultVal>
    - <valList type="closed" mode="replace">
      - <valItem ident="perg">
        <desc>parchment</desc>
      </valItem>
      - <valItem ident="chart">
        <desc>paper</desc>
      </valItem>
      - <valItem ident="mixed">
        <desc>mixture of paper and parchment, or other materials</desc>
      </valItem>
      <valItem ident="unknown" />
    </valList>
  </attDef>
</attList>
</elementSpec>
- <elementSpec ident="layout" mode="change" module="msdescription">
  - <attList>
    - <attDef ident="columns" mode="change" usage="req">
      - <datatype minOccurs="1" maxOccurs="2">
        <rng:ref name="data.count" />
      </datatype>
    </attDef>
  </attList>
</elementSpec>
- <elementSpec ident="msDesc" mode="change" module="msdescription">
  - <attList>
    <attDef ident="xml:id" mode="change" usage="req" />
    - <attDef ident="xml:lang" mode="change" usage="req">
      <defaultVal>en</defaultVal>
    </attDef>
  </attList>
</elementSpec>
- <elementSpec ident="decoNote" mode="change" module="msdescription">
  - <attList>
    - <attDef ident="type" mode="change">
      <defaultVal>other</defaultVal>
    - <valList type="closed" mode="replace">
      <valItem ident="border" />
      <valItem ident="diagram" />
      <valItem ident="initial" />
      <valItem ident="marginal" />
      <valItem ident="miniature" />
      <valItem ident="mixed" />
      <valItem ident="paratext" />
      <valItem ident="secondary" />
      <valItem ident="other" />
      <valItem ident="illustration" />
      <valItem ident="printmark" />
      <valItem ident="publishmark" />
      <valItem ident="vignette" />
      <valItem ident="frieze" />
      <valItem ident="map" />
    </valList>
  </attList>

```

```

    <!-- ADDED for WAMCP -->
    <valItem ident="unwan" />
    <!-- ADDED for WAMCP -->
    <valItem ident="rubrication" />
    <!-- ADDED for WAMCP -->
    <valItem ident="tooling" />
    <valItem ident="unspecified" />
  </valList>
</attDef>
</attList>
</elementSpec>
- <elementSpec ident="custEvent" mode="change" module="msdescription">
- <attList>
- <attDef ident="type" mode="change" usage="req">
  <defaultVal>other</defaultVal>
  - <valList type="closed" mode="replace">
    <valItem ident="check" />
    <valItem ident="conservation" />
    <valItem ident="description" />
    <valItem ident="exhibition" />
    <valItem ident="loan" />
    <valItem ident="photography" />
    <valItem ident="other" />
  </valList>
  </attDef>
</attList>
</elementSpec>
- <elementSpec ident="person" mode="change" module="namesdates">
- <attList>
- <attDef ident="sex" mode="change" usage="req">
  <defaultVal>0</defaultVal>
  </attDef>
</attList>
</elementSpec>
- <classSpec ident="att.dimensions" mode="change" type="atts">
- <attList>
  <attDef mode="delete" ident="precision" />
  - <attDef mode="change" ident="unit">
    <defaultVal>mm</defaultVal>
    - <valList type="closed" mode="replace">
      <valItem ident="cm" />
      <valItem ident="mm" />
      <valItem ident="in" />
      <valItem ident="lines" />
      <valItem ident="chars" />
    </valList>
    </attDef>
  </attList>
</classSpec>
- <elementSpec ident="dimensions" mode="change" module="msdescription">
- <attList>
- <attDef ident="type" mode="change" usage="req">
  <defaultVal>unknown</defaultVal>
  - <valList type="closed" mode="replace">
    <valItem ident="leaf" />
    <valItem ident="binding" />
    <valItem ident="slip" />
    <valItem ident="written" />
    <valItem ident="boxed" />
    <!-- ADDED for WAMCP -->
    <valItem ident="line-height" />
    <valItem ident="unknown" />
  </valList>
  </attDef>
</attList>
</elementSpec>
- <elementSpec ident="region" mode="change" module="namesdates">
- <attList>
- <attDef ident="type" mode="change" usage="req">
  <defaultVal>unknown</defaultVal>

```



```

- <valList type="closed" mode="replace">
  <valItem ident="parish" />
  <valItem ident="county" />
  <valItem ident="compass" />
  <valItem ident="geog" />
  <valItem ident="state" />
  <valItem ident="unknown" />
</valList>
</attDef>
</attList>
</elementSpec>
- <elementSpec ident="supplied" mode="change" module="transcr">
- <attList>
- <attDef ident="reason" mode="change" usage="req">
  <defaultVal>unknown</defaultVal>
- <valList type="closed" mode="replace">
  <valItem ident="omitted" />
  <valItem ident="illegible" />
  <valItem ident="damage" />
  <valItem ident="unknown" />
</valList>
</attDef>
</attList>
</elementSpec>
<!-- constrain date attributes -->
- <elementSpec ident="date" mode="change" module="core">
- <content>
- <s:pattern name="date_values">
- <s:rule context="tei:date">
  <s:assert test="@when or (@notAfter and @notBefore) or (@from and
    @to)">You must provide either @when or @to/@from, or
    @notAfter/@notBefore.</s:assert>
</s:rule>
</s:pattern>
</content>
- <attList>
  <!-- NEW FOR WAMCP -->
- <attDef ident="calendar" mode="change" usage="req">
- <valList type="semi" mode="replace">
- <valItem ident="Gregorian">
  <desc>Gregorian calendar</desc>
</valItem>
- <valItem ident="Julian">
  <desc>Julian calendar</desc>
</valItem>
- <valItem ident="AM">
  <desc>Anno Mundi</desc>
</valItem>
- <valItem ident="Hijri-shamsi">
  <desc>Hijri solar calendar (Mughal Indian revenue era)</desc>
</valItem>
- <valItem ident="Hijri-qamari">
  <desc>Hijiri lunar calendar</desc>
</valItem>
- <valItem ident="Coptic-EoM">
  <desc>Coptic (Era of Martyrs)</desc>
</valItem>
- <valItem ident="Alexandrian">
  <desc>Alexandrian (Era of Alexander I)</desc>
</valItem>
- <valItem ident="Iranian-Yazdigird">
  <desc>Era of Yazdigird (Iranian)</desc>
</valItem>
- <valItem ident="Iranian-Jalali">
  <desc>Jalali (Iranian)</desc>
</valItem>
- <valItem ident="Spanish">
  <desc>Spanish calendar</desc>
</valItem>
- <valItem ident="Ilahi">

```

```

        <desc>Ilahi (Mughal)</desc>
    </valItem>
    - <valItem ident="Hindu">
        <desc>HI ndu calendar</desc>
    </valItem>
    <valItem ident="unknown" />
    <valItem ident="other" />
</valList>
</attDef>
</attList>
</elementSpec>
<!-- remove optional global attribute we don't want to use -->
- <classSpec ident="att.global" type="atts" mode="change" module="tei">
    - <attList>
        <attDef ident="rendition" mode="delete" />
    </attList>
</classSpec>
<!-- remove stupid (non-mandatory) elements we dont want in this place -->
<!-- remove option of change within history -->
- <elementSpec xmlns:rng="http://relaxng.org/ns/structure/1.0"
    module="msdescription" ident="recordHist" mode="change">
    - <content>
        - <rng:choice>
            - <rng:oneOrMore>
                <rng:ref name="model.pLike" />
            </rng:oneOrMore>
            <rng:ref name="source" />
        </rng:choice>
    </content>
</elementSpec>
- <!--
    HERE BE DIRTY STUFF WHICH SHOULD BE IN ITS OWN NAMESPACE
    BUT WHICH IS ALREADY SCHEDULED FOR INCLUSION IN NEXT P5 RELEASE
-->
<!-- change wording of desc to be less confusing -->
- <elementSpec ident="surrogates" mode="change" module="msdescription">
    <desc>contains information about any non-digital representations of the
    manuscript being described which may exist in the holding institution or
    elsewhere.</desc>
</elementSpec>
<!-- HERE VERY DIRTY STUFF WAMCP ONLY -->
- <elementSpec ident="collection" mode="change" module="msdescription">
    - <classes mode="change">
        <memberOf mode="add" key="att.typed" />
    </classes>
    <content>
        - <rng:zeroOrMore>
            - <rng:choice>
                <rng:ref name="macro.xtext" />
                <rng:ref name="collection" />
            </rng:choice>
        </rng:zeroOrMore>
    </content>
</elementSpec>
</schemaSpec>
</div>
</body>
</text>
</TEI>

```